


Product information


CLT STANDARD DESIGNS

04/2012

C panels									
Nominal thickness [mm]	Designation [—]	Layers [—]	Lamella structure [mm]						
			C	L	C	L	C	L	
60	C3s	3	20	20	20				
80	C3s	3	30	20	30				
90	C3s	3	30	30	30				
100	C3s	3	30	40	30				
120	C3s	3	40	40	40				
100	C5s	5	20	20	20	20	20		
120	C5s	5	30	20	20	20	30		
140	C5s	5	40	20	20	20	40		
160	C5s	5	40	20	40	20	40		



L panels									
Nominal thickness [mm]	Designation [—]	Layers [—]	Lamella structure [mm]						
			L	C	L	C	L	C	
60	L3s	3	20	20	20				
80	L3s	3	30	20	30				
90	L3s	3	30	30	30				
100	L3s	3	30	40	30				
120	L3s	3	40	40	40				
100	L5s	5	20	20	20	20	20		
120	L5s	5	30	20	20	20	30		
140	L5s	5	40	20	20	20	40		
160	L5s	5	40	20	40	20	40		
180	L5s	5	40	30	40	30	40		
200	L5s	5	40	40	40	40	40		
160	L5s-2*	5	60	40	60				
180	L7s	7	30	20	30	20	30	20	30
200	L7s	7	20	40	20	40	20	40	20
240	L7s	7	30	40	30	40	30	40	30
220	L7s-2*	7	60	30	40	30	60		
240	L7s-2*	7	80	20	40	20	80		
260	L7s-2*	7	80	30	40	30	80		
280	L7s-2*	7	80	40	40	40	80		
300	L8s-2**	8	80	30	80	30	80		
320	L8s-2**	8	80	40	80	40	80		



* Cover layers consisting of 2 lengthwise layers

** Cover layers and inner layer consisting of 2 lengthwise layers

Status: 04/2012

Width (Charged widths): 245 cm, 275 cm, 295 cm

Length (Production lengths): From minimum production length of 8.00 m per charged width up to max. 16.00 m (in 10 cm increments).